



INDUSTRIAL SAFETY IDENTIFICATION Across All Industries

REFLECTIVE NUMBERS & LETTERS Binder Sheet Format, PRISMATIC GRADE, 0.75" Character

PRODUCTS & APPLICATIONS



Applications: An ideal product for use where high visibility is required in darkened areas or at night. All markers have optical lens elements enclosed with a transparent resin that has a smooth outer surface. The sheetings are intended to have a similar appearance when viewed in the daylight or by retroreflective light at night.

Sheet size: 8.5" x 10.875", with 3 hole punch (0.25" dia hole) along left edge.

Material: ASTM D4956 Type III & IV Micro-Prismatic grade reflective with pressure sensitive adhesive conforming to FP-79 (Class 1) and LS 300C (Class 1). Meets all other requirements set forth in ASTM D 4956 including Shrinkage, Flexibility, Liner removal, Adhesion, Impact resistance, specular gloss and Outdoor weathering (Types III and IV).

Application temperature: 50 °F

Service Temperature: -10 °F to +150 °F

Lifespan: Minimum outdoor lifespan of 12 years.

Stocked Color: Yellow on Black

Optional Colors (Call for Quote):



Black on Yellow



Black on White



White on Black

To Order, specify the stock number Followed by the letter or number desired. For a 2.5" character in yellow on a black background, with letter A, specify PLR156SHT-A. Binder not included.

Stock Number	Overall Marker Size (W x H)	Character Height	Sheet Size (W x H)	Colors	Markers Per Sheet	Legend
PLR156SHT	0.6" x 0.9"	0.75"	8.5" x 10.875"	Yellow on Black	156	A-Z, 0-9
PLRY156SHT	0.6" x 0.9"	0.75"	8.5" x 10.875"	Black on Yellow	156	A-Z, 0-9
PLRW156SHT	0.6" x 0.9"	0.75"	8.5" x 10.875"	Black on White	156	A-Z, 0-9
PLRWR156SHT	0.6" x 0.9"	0.75"	8.5" x 10.875"	White on Black	156	A-Z, 0-9