

INDUSTRIAL SAFETY IDENTIFICATION Across All Industries

REFLECTIVE NUMBERS & LETTERS Binder Sheet Format, PRISMATIC GRADE, 1" Character

PRODUCTS & APLICATIONS



Applications: An ideal product for use where high visibility is required in darkened areas or at night. All markers have optical lens elements enclosed with a transparent resin that has a smooth outer surface. The sheetings are intended to have a similar appearance when viewed in the daylight or by retroreflective light at night.

Sheet size: 8.5" x 11", with 5 hole punch (0.25" dia hole) on center at 1.25", 2.25", 5.5", 8.75", 9.75"

Material: ASTM D4956 Type III & IV Micro-Prismatic grade reflective with pressure sensitive adhesive conforming to FP-79 (Class 1) and LS 300C (Class 1). Meets all other requirements set forth in ASTM D 4956 including Shrinkage, Flexibility, Liner removal, Adhesion, Impact resistance, specular gloss and Outdoor weathering (Types III and IV).

Application temperature: 50°F

Service Temperature: -10°F to +150°F

Lifespan: Minimum outdoor lifespan of 12 years.

Stocked Color: Yellow on Black

Optional Colors (Call for Quote):







Black on White



White on Black

To Order, specify the stock number Followed by the letter or number desired. For a 2.5" character in yellow on a black background, with letter A, specify PLR70SHT-A. Binder not included.

Stock Number	Overall Marker Size (W x H)	Character Height	Sheet Size (W x H)	Colors	Markers Per Sheet	Legend
PLR70SHT	1.1" x 1.1"	1"	8.5" x 11"	Yellow on Black	70	A-Z, 0-9
PLRY70SHT	1.1" x 1.1"	1"	8.5" x 11"	Black on Yellow	70	A-Z, 0-9
PLRW70SHT	1.1" x 1.1"	1"	8.5" x 11"	Black on White	70	A-Z, 0-9
PLRWR70SHT	1.1" x 1.1"	1"	8.5" x 11"	White on Black	70	A-Z, 0-9

