



# INDUSTRIAL SAFETY IDENTIFICATION Across All Industries

## REFLECTIVE NUMBERS & LETTERS Binder Sheet Format, PRISMATIC GRADE, 2.5" Character

### PRODUCTS & APPLICATIONS



**Applications:** An ideal product for use where high visibility is required in darkened areas or at night. All markers have optical lens elements enclosed with a transparent resin that has a smooth outer surface. The sheetings are intended to have a similar appearance when viewed in the daylight or by retroreflective light at night.

**Sheet size:** 7.875" x 11.37", with 3 hole punch (0.25" dia hole) along left edge.

**Material:** ASTM D4956 Type III & IV Micro-Prismatic grade reflective with pressure sensitive adhesive conforming to FP-79 (Class 1) and LS 300C (Class 1). Meets all other requirements set forth in ASTM D 4956 including Shrinkage, Flexibility, Liner removal, Adhesion, Impact resistance, specular gloss and Outdoor weathering (Types III and IV).

**Application temperature:** 50°F

**Service Temperature:** -10°F to +150°F

**Lifespan:** Minimum outdoor lifespan of 12 years.

**Stocked Color:** Yellow on Black

**Optional Colors (Call for Quote):**



Black on Yellow



Black on White



White on Black

To Order, specify the stock number Followed by the letter or number desired. For a 2.5" character in yellow on a black background, with letter A, specify PLR16SHT-A. Binder not included.

Stock Number	Overall Marker Size (W x H)	Character Height	Sheet Size (W x H)	Colors	Markers Per Sheet	Legend
PLR16SHT	1.75" x 2.84"	2.5"	7.875" x 11.37"	Yellow on Black	16	A-Z, 0-9
PLRY16SHT	1.75" x 2.84"	2.5"	7.875" x 11.37"	Black on Yellow	16	A-Z, 0-9
PLRW16SHT	1.75" x 2.84"	2.5"	7.875" x 11.37"	Black on White	16	A-Z, 0-9
PLRWR16SHT	1.75" x 2.84"	2.5"	7.875" x 11.37"	White on Black	16	A-Z, 0-9